

**DIMENSIONI BCG**

DIN 46397-11

	d 1	d 2	d 3	d 4	d 5	e 1	t 5	L1	L2
BCG31	315	180	160	127	16	100	2	236	200
		200							
		224							
BCG35	355	200	160	127	16	100	2	212	180
		224						265	224
		250							
BCG40	400	224	160	127	28	100	2	236	200
		250						300	250
		280							
BCG45	450	250	160	127	28	100	2	265	224
		280						335	280
		315							
BCG50	500	280	160	127	28	100	2	300	250
		315						375	315
		355							
BCG56	560	315	160	127	28	100	2	335	280
		355						425	355
		400							
BCG63	630	355	160	127	28	100	2	375	315
		400						475	400
		450							
BCG71	710	400	300	250	40	170	2.5	425	355
		450						530	450

		500							
BCG80	800	450	300	250	40	170	2.5	475	400
		500						600	500
		560							
BCG10	1000	560	300	250	50	250	2.5	750	630
		630							
		710							

**DIN 46395**

	d 1	d 2	d 3	d 4	d 5	e 1	11	12
BCG31	315	125	71	36	8 to 16	71	236	200
		160					190	160
BCG35	355	140	112	56	16 to 28	112	265	224
		180					215	180
BCG40	400	160	112	56	16 to 28	112	300	250
		200					236	200
BCG45	450	180	112	56	16 to 28	112	335	280
		224					265	224

BCG50	500	200	112	56	16 to 28	140	375	315
		250					300	250
BCG56	560	224	112	56	16 to 28	140	425	355
		280					335	280
BCG63	630	250	112	56	16 to 28	140	475	400
		315					375	315
BCG71	710	355	160	80	28 to 40	160	530	450
BCG80	800	400	160	80	28 to 40	160	600	500
BCG90	900	450	160	80	28 to 40	160	670	560
BCG10	1000	500	160	80	28 to 40	160	750	630

Le dimensioni sopra riportate fanno riferimento rispettivamente alla norma DIN **46397-11: 2005-07** e **46395**.

Le bobine BCG sono disponibili anche con diametro flangia 600 e 760 (non presenti tra gli standard DIN) e altre dimensioni secondo specifica del cliente.