

DIMENSIONI BCS

DIN 46397-11

	d 1	d 2	d 3	d 4	d 5	e 1	t 5	L1	L2		
BCS80	800	450	300	250	40	170	2.5	475	400		
		500						600	500		
		560									
BCS10	1000	560	300	250	50	250	2.5	750	630		
		630									
		710									
BCS12	1250	710	300	250	50	250	2.5	950	800		
		800									
		900									

DIN 46395

	d 1	d 2	d 3	d 4	d 5	e 1	l 1	l 2
BCS80	800	400	160	80	28 to 40	160	600	500
BCS90	900	450	160	80	28 to 40	160	670	560

BCS10	1000	500	160	80	28 to 40	160	750	630
BCS11	1120	560	160	80	28 to 40	160	850	710
BCS12	1250	630	160	80	28 to 40	160	950	800
BCS14	1400	710	160	80	40 to 63	300	1060	900
BCS16	1600	800	160	80	40 to 63	300	1180	1000
BCS18	1800	1000	200	100	40 to 63	300	1320	1120
BCS20	2000	1120	200	100	40 to 63	300	1500	1250
BCS22	2240	1250	250	125	40 to 63	300	1700	1400
BCS25	2500	1500	250	125	40 to 63	300	1900	1600
BCS28	2800	1800	280	140	40 to 63	300	2120	1800

46391-1: 2005-04

	d 1	d 2	d 4	d5	e 1	1 1	1 2
BCS80	800	400	80	40	100	550	400
BCS90	900	450	80	50	160	710	560
BCS10	1000	500	80	50	160	710	560
BCS12	1250	630	80	65	160	900	710
BCS14	1400	710	80	65	160	900	710
BCS16	1600	800	80	65	300	1120	900
BCG18	1800	1000	125	65	300	1120	900
BCS20	2000	1000	125	65	300	1360	1120
		1250	125	65	300		
BCS22	2240	1120	125	65	400	1360	1120
		1400	125	65	400	1450	1220

BCS25	2500	1250	125	65	400	1360	1120
		1400	125	65	400	1450	1220
		1600	125	65	400		
BCS28	2800	1800	125	65	600	1650	1380
BCS30	3000	1800	140	65	600	2000	1600
		2000					
BCS31	3150	1800	140	65	600	2000	1600
		2000					
BCS33	3350	2000	140	65	600	2000	1600
		2360					
BCS35	3550	2000	140	65	600	2000	1600
		2360					
BCS37	3750	2360	200	80	1000	2240	1800
		2650					
BCS40	4000	2650	200	80	1000	2240	1800
		2800					
BCS42	4250	2650	200	80	1000	2500	2000
		2800					
BCS45	4500	2800	200	80	1000	2500	2000



Le dimensioni sopra riportate fanno riferimento rispettivamente alla norma DIN **46397-11: 2005-07, 46395, 46391-1: 2005-04.**

Le bobine sono disponibili con diametro flangia anche inferiori a 800mm e fino ad un massimo di 4500 mm.