

**DIMENSIONI BFA**

**DIN 46397-11**

	d 1	d 2	d 3	d 4	d 5	e 1	t 5	L1	L2		
BFA80	800	450	300	250	40	170	2.5	475	400		
		500						600	500		
		560									
BFA10	1000	560	300	250	50	250	2.5	750	630		
		630									
		710									
BFA12	1250	710	300	250	50	250	2.5	950	800		
		800									
		900									

**DIN 46395**

	d 1	d 2	d 3	d 4	d 5	e 1	l 1	l 2
BFA80	800	400	160	80	28 to 40	160	600	500
BFA90	900	450	160	80	28 to 40	160	670	560

BFA10	1000	500	160	80	28 to 40	160	750	630
BFA11	1120	560	160	80	28 to 40	160	850	710
BFA12	1250	630	160	80	28 to 40	160	950	800
BFA14	1400	710	160	80	40 to 63	300	1060	900
BFA16	1600	800	160	80	40 to 63	300	1180	1000
BFA18	1800	1000	200	100	40 to 63	300	1320	1120
BFA20	2000	1120	200	100	40 to 63	300	1500	1250
BFA22	2240	1250	250	125	40 to 63	300	1700	1400
BFA25	2500	1500	250	125	40 to 63	300	1900	1600
BFA28	2800	1800	280	140	40 to 63	300	2120	1800

46391-1: 2005-04

	d 1	d 2	d 4	d 5	e 1	l 1	l 2
BFA80	800	400	80	40	100	550	400
BFA90	900	450	80	50	160	710	560
BFA10	1000	500	80	50	160	710	560
BFA12	1250	630	80	65	160	900	710
BFA14	1400	710	80	65	160	900	710
BFA16	1600	800	80	65	300	1120	900
BFA18	1800	1000	125	65	300	1120	900
BFA20	2000	1000 1250	125 125	65 65	300 300	1360	1120
BFA22	2240	1120	125	65	400	1360	1120

		1400	125	65	400	1450	1220
BFA25	2500	1250	125	65	400	1360	1120
		1400	125	65	400	1450	1220
		1600	125	65	400		
BFA28	2800	1800	125	65	600	1650	1380
BFA30	3000	1800	140	65	600	2000	1600
		2000					
BFA31	3150	1800	140	65	600	2000	1600
		2000					
BFA33	3350	2000	140	65	600	2000	1600
		2360					
BFA35	3550	2000	140	65	600	2000	1600
		2360					
BFA37	3750	2360	200	80	1000	2240	1800
		2650					
BFA40	4000	2650	200	80	1000	2240	1800
		2800					
		3000					

Le dimensioni sopra riportate fanno riferimento rispettivamente alla norma DIN **46397-11: 2005-07, 46395, 46391-1: 2005-04**.

Le bobine sono disponibili con diametro flangia anche inferiori a 800mm e fino ad un massimo di 4000 mm.

